



Main Propulsion for the Ares Projects

Phil Sumrall

Advanced Planning Manager

Ares Projects

NASA MSFC

Baylor University

April 21, 2009





- ◆ **The NASA Ares Projects Office is developing the launch vehicles to support exploration beyond low earth orbit for decades to come**
- ◆ **Ares I is a crewed vehicle, and Ares V is a heavy lift vehicle being designed to launch cargo into LEO and transfer cargo and crews to the Moon**
- ◆ **The performance, reliability, operability, and cost of the Ares propulsion systems are critical to everything we aspire to do.**
- ◆ **Ares propulsion systems are based on heritage hardware and experience from Apollo to the Space Shuttle to current ELVs**
- ◆ **My goal today is to update you on the status of Ares propulsion systems**



Our Exploration Fleet

What Will the Vehicles Look Like?




Earth Departure Stage



**Orion
Crew Exploration
Vehicle**



**Ares V
Cargo Launch
Vehicle**



**Ares I
Crew Launch
Vehicle**




**Altair
Lunar
Lander**





Building on a Foundation of Proven Technologies


- Launch Vehicle Comparisons -



Ares Vehicles: Commonality & Heritage Hardware




Note: Vehicles not to scale






Ares I Elements





First Stage



Mass: 733 mT (1,616 lbm)

Thrust: 15.8 MN


Burn Duration: 126 sec

Height: 53 m (174 ft)

Diameter: 3.7 m (12 ft)



Upper Stage



Propellant Load: 138 mT (304K lbm)
Total Mass: 156 mT (344K lbm)
Dry Mass: 16.3 mT (36K lbm)
Dry Mass (Interstage): 4.1 mT (9K lbm)
Length: 25.6 m (84 ft)
Diameter: 5.5 m (18 ft)
LOX Tank Pressure: 50 psig
LH₂ Tank Pressure: 42 psig

J-2X Upper Stage Engine for Ares I and Ares V



◆ Upper Stage Engine Element challenge:

Design an engine...



based on an evolution of the Apollo/Saturn era J-2 (GG cycle, 230,000 lbf, 424 seconds I_{sp})...

increased to 294,000 lbf (1.3M Newtons) thrust...

increased to 448 seconds of specific impulse (highest ever I_{sp} for an engine of this class) ...

nearly two years faster than an engine of this class has been developed...


and make it work for two different vehicles with two different missions, keeping as much commonality as possible.





J-2X Engine

Used on Ares I and Ares V



Turbomachinery

- Based on J-2S MK-29 design

Flexible Inlet Ducts

- Based on J-2 & J-2S ducts

Gas Generator

- Based on RS-68 design

Open-Loop Pneumatic Control

- Similar to J-2

Engine Controller

- Based directly on RS-68 design and software architecture

HIP-bonded MCC

- Based on RS-68 demonstrated technology

Regeneratively Cooled Nozzle Section

- Based on long history of RS-27 success

Metallic Nozzle Extension

- New design

Mass: 2.5 mT (5,511 lbm)

Height: 4.7 m (15.4 ft)

Diameter: 3.05 m (10 ft)

Thrust: 1,308K N (294K lbm) (vac)

Isp: 448 sec (vac)

Height: 4.7 m (15.4 ft)

Diameter: 3.05 m (10 ft)

Operation Time: 500 sec.

Altitude Start / On-orbit Restart

Operational Life: 8 starts/ 2,600 sec




Pratt & Whitney

A United Technologies Company

Pratt & Whitney Rocketdyne, Inc.



Ares V Elements



RS-68 to RS-68B



* Redesigned turbine nozzles to increase maximum power level by $\approx 2\%$

Helium spin-start duct redesign, along with start sequence modifications, to help minimize pre-ignition free hydrogen

Redesigned turbine seals to significantly reduce helium usage for pre-launch


* Higher element density main injector improving specific impulse by $\approx 2\%$ and thrust by $\approx 4\%$

♦ Other RS-68A upgrades or changes that may be included:

- Bearing material change
- New Gas Generator igniter design
- Improved Oxidizer Turbo Pump temp sensor
- Improved hot gas sensor
- 2nd stage Fuel Turbo Pump blisk crack mitigation
- Cavitation suppression
- ECU parts upgrade

Increased duration capability ablative nozzle

* RS-68A Upgrades





What Progress Have We Made?



◆ Ares I

- Ares I, First Stage, & Upper Stage PDRs complete in '08
- Numerous First Stage development and static motor casting & firing tests, wind tunnel, nozzle, materials, parachute drop tests complete
- All Ares I-X hardware at KSC for '09 launch




◆ J-2X

- Completed PDR in '07, CDR in '08
- SSC A-1 test stand converted, A-3 stand construction under way to support J-2X
- Numerous heritage, component, subscale, and powerpack tests and CFD completed in support of turbomachinery, combustion devices, etc.
- Casting/machining trials under way/long-lead parts procured




◆ Ares V

- Subscale main injector tests, analysis conducted on RS-68B
- LCCR establishes POD concept '08
- RFP for concept definition issued '09



For more information go to www.nasa.gov/ares



www.nasa.gov/ares